



Crystal Merchandiser® RVMC24, RVMC30 with Single-Swing Doors

Model	Nominal Length	Color Temp (K)	Location	Rated Input	CRI	Lumens (TYP @ 4000K)	Wattage (TYP)	Efficacy (Lumens/Watt)
ChillBrite 4234	70"	3000, 3500, 4000	Left/Right	24 VDC	92	968 lm	8.8W	110
ChillBrite 4234	70"	3000, 3500, 4000	Center	24 VDC	92	2,024 lm	17.6W	115

Crystal Merchandiser® RVMC24 with French-Swing Doors

Model	Nominal Length	Color Temp (K)	Location	Rated Input	CRI	Lumens (TYP @ 4000K)	Wattage (TYP)	Efficacy (Lumens/Watt)
ChillBrite 4234	70"	3000, 3500, 4000	Left/Right	24 VDC	92	1,795 lm	17.6W	102
ChillBrite 4234	70"	3000, 3500, 4000	Center	24 VDC	92	3,872 lm	35.2W	110

Highlight Merchandiser® RHMC30, RHLC30 with Single-Swing Doors

Model	Nominal Length	Color Temp (K)	Location	Rated Input	CRI	Lumens (TYP @ 4000K)	Wattage (TYP)	Efficacy (Lumens/Watt)
ChillBrite 4190	62"	3500, 4000	Left/Right	24 VDC	90	792 lm	8.0W	99
ChillBrite 4190	62"	3500, 4000	Center	24 VDC	90	1,584 lm	16.0W	99

Crystal Merchandiser® RVLC30 & Highlight Merchandiser® RHMC30T, RHLC30T with Single-Swing Doors

Model	Nominal Length	Color Temp (K)	Location	Rated Input	CRI	Lumens (TYP @ 4000K)	Wattage (TYP)	Efficacy (Lumens/Watt)
ChillBrite 4190	67"	3500, 4000	Left/Right	24 VDC	90	864 lm	9.0W	96
ChillBrite 4190	67"	3500, 4000	Center	24 VDC	90	1,728 lm	18.0W	96

Reveal Merchandiser® with Doors ORMC83D & Highlight Merchandiser® RHCC24 with French-Swing Doors

Model	Nominal Length	Color Temp (K)	Location	Rated Input	CRI	Lumens (TYP @ 4000K)	Wattage (TYP)	Efficacy (Lumens/Watt)
ChillBrite 4211	62"	3000, 3500, 4000	Left/Right	24 VDC	90	1,760 lm	17.6W	100
ChillBrite 4211	62"	3000, 3500, 4000	Center	24 VDC	90	3,520 lm	35.2W	100

Reveal Merchandiser® with Doors ORMC88D with French-Swing Doors

Model	Nominal Length	Color Temp (K)	Location	Rated Input	CRI	Lumens (TYP @ 4000K)	Wattage (TYP)	Efficacy (Lumens/Watt)
ChillBrite 4211	67"	3000, 3500, 4000	Left/Right	24 VDC	90	1,920 lm	19.2W	100
ChillBrite 4211	67"	3000, 3500, 4000	Center	24 VDC	90	3,840 lm	38.4W	100

Reveal Merchandiser® ORMC75, ORMC80, ORMC82, ORMC87 Canopy Lights

Model	Nominal Length	Color Temp (K)	Location	Rated Input	CRI	Lumens (TYP @ 4000K)	Wattage (TYP)	Efficacy (Lumens/Watt)
ChillBrite 4249	35"	3000, 3500, 4000	Canopy	24 VDC	90	1,500	15.0W	100
ChillBrite 4249	47"	3000, 3500, 4000	Canopy	24 VDC	90	2,000	20.0W	100

Features:

1. Anti-glare design.
2. Elegant appearance.
3. Bright and consistent illuminance of display area.
4. Less heat radiation, more energy saving.
5. Optional PWM controller with dimming and on/off control for energy savings.
6. Works with motion sensor (occupancy sensor).
7. Lifetime: 50,000 hrs (Ta=95°F, 35°C).
8. IP Rating: IP65 (dust tight, protection from water jets).
9. Ta: -13°F to ~95°F (-25°C to ~35°C).
10. Material: Aluminum alloy.

Warranty:

1. LED Light: 5 Years Parts
2. LED Power Supply: 5 Years Parts

SS-60-I

Specifications are subject to change without notice.

2/11/2025





Reveal Merchandiser® ORMC75, ORMC80, ORMC82, ORMC87 Sill Lights

Model	Nominal Length	Color Temp (K)	Location	Rated Input	CRI	Lumens (TYP @ 4000K)	Wattage (TYP)	Efficacy (Lumens/Watt)
ChillBrite 4251	35"	3000, 3500, 4000	Sill	24 VDC	90	900	7.5W	120
ChillBrite 4251	47"	3000, 3500, 4000	Sill	24 VDC	90	1,200	10.0W	120

Reveal Merchandiser® ORMC75, ORMC80, ORMC82, ORMC87 Under Shelf Lights

Model	Nominal Length	Color Temp (K)	Location	Rated Input	CRI	Lumens (TYP @ 4000K)	Wattage (TYP)	Efficacy (Lumens/Watt)
ChillBrite 4250	35"	3000, 3500, 4000	Under Shelf	24 VDC	90	450	3.75W	120
ChillBrite 4250	47"	3000, 3500, 4000	Under Shelf	24 VDC	90	600	5.0W	120

Highlight Merchandiser® RHMC30, RHLC30 with Single-Swing Doors

Model	Nominal Length	Color Temp (K)	Location	Rated Input	CRI	Lumens (TYP @ 4000K)	Wattage (TYP)	Efficacy (Lumens/Watt)
ChillBrite 4244	62"	3700, 4000, 4300	Left/Right	24 VDC	92	960 lm	8.0W	120
ChillBrite 4244	62"	3700, 4000, 4300	Center	24 VDC	92	1,760 lm	16.0W	110

Crystal Merchandiser® RVLC30 & Highlight Merchandiser® RHMC30T, RHLC30T with Single-Swing Doors

Model	Nominal Length	Color Temp (K)	Location	Rated Input	CRI	Lumens (TYP @ 4000K)	Wattage (TYP)	Efficacy (Lumens/Watt)
ChillBrite 4244	67"	3700, 4000, 4300	Left/Right	24 VDC	92	968 lm	9.0W	108
ChillBrite 4244	67"	3700, 4000, 4300	Center	24 VDC	92	1,936 lm	17.6W	110

Guardian Merchandiser® CGMC30, CGLC30 with Single-Swing Doors

Model	Nominal Length	Color Temp (K)	Location	Rated Input	CRI	Lumens (TYP @ 4000K)	Wattage (TYP)	Efficacy (Lumens/Watt)
ChillBrite 4265	62"	4000	Left/Right	24 VDC	92	900 lm	6.4W	140
ChillBrite 4265	62"	4000	Center	24 VDC	92	1,790 lm	12.8W	140

Guardian Merchandiser® CGMC30, CGLC30 with Single-Swing Doors

Model	Nominal Length	Color Temp (K)	Location	Rated Input	CRI	Lumens (TYP @ 4000K)	Wattage (TYP)	Efficacy (Lumens/Watt)
ChillBrite 4266	62"	4000	Left/Right	24 VDC	92	800 lm	6W	135
ChillBrite 4266	62"	4000	Center	24 VDC	92	1,740 lm	12W	145

Features:

- Anti-glare design.
- Elegant appearance.
- Bright and consistent illuminance of display area.
- Less heat radiation, more energy saving.
- Optional PWM controller with dimming and on/off control for energy savings.
- Works with motion sensor (occupancy sensor).
- Lifetime: 50,000 hrs (Ta=95°F, 35°C).
- IP Rating: IP65 (dust tight, protection from water jets).
- Ta: -13°F to -95°F (-25°C to -35°C).
- LED Body Material: Aluminum alloy.
- Undershelf lights have integrated mounting magnets.

Warranty:

- LED Light: 5 Years Parts
- LED Power Supply: 5 Years Parts

SS-60-I

Specifications are subject to change without notice.

2/11/2025



Intertek