



GUARDIAN[®]

merchandise



Product Catalog

DAIRY | DELI | PRODUCE | FRESH MEAT | BEVERAGE | FROZEN FOOD | ICE CREAM



TABLE OF CONTENTS

■ Overview	4-5
■ Features and Options	6-8
■ Applications	9
■ Nomenclature	10-11
■ Spec Sheets	12-17

GUARDIAN[®]

merchandise

CGLC30 • CGMC30

Top Mounted Packaged
Refrigeration Unit (PRU)


Left Door Swing

6' ChillBrite[®]
4000K LED Lighting

CoolView[®] Envision[®] Doors
30"x68" argon-filled

Five 24" Shelves
(per door)

23.5" Bottom Wire Rack



GUARDIAN[®]

merchandiser

The Guardian[®] Merchandiser is a full sized, self-contained propane solution designed with versatility and efficiency in mind. Ideal for dollar stores and small format retail stores, the Guardian[®] delivers reliable performance in your store's footprint.

PROPANE

The Guardian[®] utilizes propane, a zero ozone depleting refrigerant that is highly efficient and a future-proof option.

SELF-CONTAINED

Roof-mounted packaged refrigeration unit (PRU) cools the case, so there is no need for a separate refrigeration system.

PLUG-AND-PLAY

Guide the Packaged Refrigeration Unit (PRU) into its base, bolt it down, & plug it in for quick installation & start up.

FORKLIFTABLE

Forkliftable from either side of the case, our reinforced bottom assembly features steel forklift plates, saving time from unloading the case and streamlining the installation process.





5CGLC30



3CGMC30-P

REVERSE AIRFLOW

Reverse airflow reduces frost on products and doors, ensuring clear visibility and product integrity.

DOORS

Standard CoolView® Envision® 30" x 68" doors. Designed to resist condensation and sweating.

HANDLES

CoolArc® Crescent™ handles in black.

LIGHTING

ChillBrite® custom-designed 4000K LED lights with equal dispersion.

NATURAL SOLUTION

Genesys® Natural refrigerant solutions now available in R-290 (Propane).

INSTALLATION FRIENDLY

Designed for effortless installation. This case fits through standard 80" doorways and moves easily from truck to store via forklift, streamlining setup.

Features and Options

Interior

	CGLC30	CGMC30
1 Interior Color White	STANDARD	STANDARD
2 Lighting ChillBrite® 4000K	STANDARD	STANDARD
3 Shelving 30" x 24" Solid Universal, White (2-position)	STANDARD	STANDARD
4 Price Tag Molding White PVC per Shelf & Rack	STANDARD	STANDARD
5 Bottom Wire Rack 30" x 23.5" w/ 2" Lip, White	STANDARD	STANDARD



5CGMC30-B

STANDARD: basic features & normal lead times

Optional: additional features available & normal lead times

Special: custom features & increased lead time

Doors

6 Door Type

Black

CGLC30

STANDARD

CGMC30

STANDARD

7 Door Handle

Classic™, Black

STANDARD

STANDARD

8 Door Swing

Left | Handle on Right

STANDARD

STANDARD

Exterior

9 Exterior Color

Black ZZ-000

STANDARD

STANDARD

White ZZ-100

Optional

Optional

Filler-to-Wall Panel

12"

Optional

Optional

16" (Seismic)

Optional

Optional

Controls

Electronic Defrost Controller

Dixell XR60

STANDARD

STANDARD

Refrigeration

	CGLC30	CGMC30
Refrigeration Connection		
Self-Contained	STANDARD	STANDARD
Defrost Type		
Hot Gas	STANDARD	STANDARD
Refrigerant		
R-290 (Propane)	STANDARD	STANDARD

Electrical

	CGLC30	CGMC30
Electrical Service		
120V - 1PH - 60HZ		STANDARD
120/208V - 1PH - 60HZ	STANDARD	

Other Features

	CGLC30	CGMC30
Also Available		
Seismic Package	Optional	Optional

STANDARD: basic features & normal lead times

Optional: additional features available & normal lead times

Special: custom features & increased lead time

GUARDIAN[®]

merchandiser
CGLC30 • CGMC30

The Guardian[®] Merchandiser is a full-sized, self-contained propane solution engineered for maximum versatility and operational efficiency. Whether you're outfitting a dollar store, or any small-format retail space, the Guardian[®] adapts seamlessly to your footprint.

Perfect for end caps, remodel stand-ins, and tight merchandising zones, this unit delivers dependable performance without compromising space. Its sleek design and plug-and-play functionality make it an ideal choice for retailers.

From convenience aisles to produce sections, the Guardian[®] is your go-to merchandising solution—where reliability meets retail flexibility.



END CAPS



Perfect for promotional items, grab-and-go products, or seasonal features—this end cap solution boosts product visibility, drives impulse sales, and has a compact design for flexible store placement.

PICKUP



Keeping groceries at the right temperature and neatly sorted, our solutions are easy to install in pickup zones. This enables quick, accurate pickups with minimal wait time for customers.

RENOVATIONS



Great for temporary placement, our solutions keep your merchandise accessible and organized throughout the remodel process. With flexible, quick installation, you can seamlessly transfer cases between stores during renovations.



NOMENCLATURE

The Guardian® Merchandiser is a self-contained display case designed to support a wide range of product categories. Its flexible applications include produce, dairy, deli, beverages, ice cream, fresh meat, and frozen foods, making it a versatile solution for diverse merchandising needs. Featuring CoolView® Envision® doors, the unit offers maximum product visibility with a nearly invisible frame—drawing customer attention directly to your inventory and enhancing the overall shopping experience.

4CGMC

①

②

① **Number of Doors**
2, 3, 4, 5

② **Type of Case**
C = Self-Contained
G = Guardian® Merchandiser
M/L – Medium or Low Temp
C – Cantilever Shelving



CGLC30



CGMC30

30-B

③ ④

THE
GUARDIAN[®]
merchandise



③ **Door Width in Inches**
30 = 30" Standard Swing

④ **Applications**
B = Beverage
D = Dairy/ Deli
M = Meat
P = Produce

BEHIND THE SHROUD

THE PACKAGED REFRIGERATION UNIT (PRU)

- Less than 80lbs, easy for two people to slide into place using guide rails to ensure positive lock.
- Standard 13" Shroud shipped with every case to conceal the PRU.
- Setting and installation of PRU
 - » No quick connects
 - » Plug 'n play (cord connected)
 - » Self-contained condensate (no field install)



GUARDIAN
merchandiser

Guardian® Merchandiser CGMC30 Specs

Medium Temp Reach-In Display Cases

2-Door, 3-Door, 4-Door, and 5-Door Cases

Quick Specs

Energy Usage (5-Door Daily)*

Standard: 14.5 kWh

Merchandising (4-Door)

Facings: 71.8 ft²

Packout: 143.4 ft³ with 30" wide x 24" deep shelves

Features

Go Green

Propane (R-290) is an environmentally friendly and natural refrigerant.

CoolView® Doors

30" wide x 68" tall CoolView® Envision® Doors

LED Lighting

ChillBrite® 4000K LED Lighting

Additional Models

The Guardian® Merchandiser is also available in low temp.

Continuous Lineup

Unlike traditional self-contained display cases, these grocery style merchandisers can be joined to make one continuous lineup.

Applications



Beverage




Dairy



Deli



Produce



Manuals and Instructions:
<https://www.zero-zone.com/cglc-cgmc>



Contact Us:

800-247-4496

www.zero-zone.com

Specifications are subject to change without notice. All dimensions are nominal.
Case designed to operate in an ambient temperature of 75°F and relative humidity of 55% or lower.



SS-136 Rev A • 5/20/2026

© 2026 Zero Zone, Inc.

Page 1 of 3






Standard Package

Refrigeration Data	R-290 Refrigerant			
	2-Door	3-Door	4-Door	5-Door
Number of PRUs	1	2	2	3
Refrigerant Charge (g) ¹	120	240	240	360
Zero Zone PRU Unit #	69-0875-02	69-0875-02	69-0875-02	69-0875-02
Total Weight of PRU(s) (lbs.) ²	70	140	140	210
Electrical & Energy Data ^{3,4}	2-Door	3-Door	4-Door	5-Door
Daily Energy Use (kWh)	5.6	8.2	12.6	14.5
Amps (a)	3.9	6.9	6.9	9.9
Voltage/Phase/Frequency	120V-1PH-60Hz	120V-1PH-60Hz	120V-1PH-60Hz	120V-1PH-60Hz
NEMA Configuration	L5-20P	L5-20P	L5-20P	L5-20P
Rejected Heat (Btu/h) ⁵	800	1160	1275	2060

Physical Data

Case Calculations	2-Door	3-Door	4-Door	5-Door
Facings (ft. ²)	28.7	42.5	57.3	71.8
Packout (ft. ³) 24" Shelves	57.3	86	114.7	143.4
Weight (lbs.) ⁶	630	900	1,160	1,510


CGLC30 Packaged Refrigeration Unit (PRU) Top View



- Notes:**
1. Refrigerant charge includes combined Packaged Refrigeration Unit.
 2. Two people are required to safely lift a single PRU.
 3. Data based on Zero Zone ChillBrite® 4000K LED lighting, Zero Zone CoolView® Envision® doors.
 4. 208V (four-wire) service; 115/208V-1PH-60Hz; red and black AC Line, white AC neutral, green Safety Ground.
 5. Adequate ventilation must be provided to dissipate rejected heat from the top of the unit for proper performance. Clearance of less than 30" above the top of the shroud to the ceiling requires special design considerations. See Zero Zone self-contained Installation & Operation Manual for specific details.
 6. Does not include weight of packaged refrigeration unit. Weights include 2 end panels at 60 lbs. per pair.
 7. No floor drain or condensate pump/pan needed. Condensate is routed through a discharge line to the trap, where it evaporates.




CGMC30 Guardian® Top View



Measurements	2-Door	3-Door	4-Door	5-Door
Case Length (in.) without End Panels	60 7/8	91 3/8	121 3/4	152 1/4
Case Length (in.) with End Panels	65 7/8	96 3/8	126 3/4	157 1/4

CGMC30 Guardian® End View





GUARDIAN
merchandiser

Guardian® Merchandiser CGLC30 Specs

Low Temp Reach-In Display Cases

2-Door, 3-Door, 4-Door, and 5-Door Cases

Quick Specs

Energy Usage (5-Door Daily)*
Standard: 42 kWh

Merchandising (5-Door)
Facings: 71.8 ft²
Packout: 143.4 ft³ with 30" wide x 24" deep shelves

Features

Go Green

Propane (R-290) is an environmentally friendly and natural refrigerant.

CoolView® Doors

30" wide x 68" tall CoolView® Envision® Doors

LED Lighting

ChillBrite® 4000K LED Lighting

Additional Models

The Guardian® Merchandiser is also available in medium temp.

Continuous Lineup

Unlike traditional self-contained display cases, these grocery style merchandisers can be joined to make one continuous lineup.


Applications



Ice Cream



Frozen Food



Manuals and Instructions:
<https://www.zero-zone.com/cglc-cgmc>



Contact Us:

800-247-4496
www.zero-zone.com

Specifications are subject to change without notice. All dimensions are nominal.
Case designed to operate in an ambient temperature of 75°F and relative humidity of 55% or lower.



SS-135 Rev A • 5/20/2026
© 2026 Zero Zone, Inc.
Page 1 of 3





Standard Package

Refrigeration Data
Number of PRUs
Refrigerant Charge (g) ¹
Zero Zone PRU Unit #
Total Weight of PRU(s) (lbs.) ²
Electrical & Energy Data ^{3, 4}
Daily Energy Use (kWh)
Amps (a)
Voltage/Phase/Frequency
NEMA Configuration
Rejected Heat (Btu/h) ⁵


R-290 Refrigerant			
2-Door	3-Door	4-Door	5-Door
1	2	2	3
135	270	270	360
69-0875-01	69-0875-01	69-0875-01	69-0875-01
85	170	170	255
2-Door	3-Door	4-Door	5-Door
16	25	31.8	42
9.6	11.3	11.3	15.9
120/208V-1Ph-60Hz	120/208V-1Ph-60Hz	120/208V-1Ph-60Hz	120/208V-1Ph-60Hz
L14-20P	L14-20P	L14-20P	L14-20P
2485	3710	4730	5970

Physical Data

Case Calculations
Facings (ft. ²)
Packout (ft. ³) 24" Shelves
Weight (lbs.) ⁶ without End Panels

2-Door	3-Door	4-Door	5-Door
28.7	42.5	57.3	71.8
57.3	86	114.7	143.4
630	900	1,160	1,510


CGLC30 Packaged Refrigeration Unit (PRU) Top View



- Notes:**
1. Refrigerant charge includes combined Packaged Refrigeration Unit.
 2. Two people are required to lift a single PRU.
 3. Data based on Zero Zone ChillBrite® 4000K LED lighting, Zero Zone CoolView® Envision® doors.
 4. 208V (four-wire) service; 115/208V-1PH-60Hz; red and black AC Line, white AC neutral, green Safety Ground.
 5. Adequate ventilation must be provided to dissipate rejected heat from the top of the unit for proper performance. Clearance of less than 30" above the top of the shroud to the ceiling requires special design considerations. See Zero Zone self-contained Installation & Operation Manual for specific details.
 6. Does not include weight of packaged refrigeration unit. Weights include 2 end panels at 60 lbs. per pair.
 7. No floor drain or condensate pump/pan needed. Condensate is routed through a discharge line to the trap, where it evaporates.




CGLC30 Top View



Measurements	2-Door	3-Door	4-Door	5-Door
Case Length (in.) without End Panels	60 7/8	91 3/8	121 3/4	152 1/4
Case Length (in.) with End Panels	65 7/8	96 3/8	126 3/4	157 1/4

CGLC30 End View





the responsive company™

zero-zone.com • 800-247-4496

Connect with Us!



ZERO ZONE, INC. • ZERO-ZONE.COM
CASE & SYSTEMS • 800-247-4496
© 2026 Zero Zone, Inc. • NOV 2025



1-YEAR PARTS
10-YEAR GLASS PACK
5-YEAR LED PARTS

